SPEED TECH™

CHEMBOND

Jara Hatke®



- Tile Adhesive
- Tile Grout
- Epoxy Grout
- Tiles Cleaner
- Grout Admix
- Spacer & Leveler

Complete Solution Of The Construction Chemical

SPEED TECH™
CHEMBOND

About us

SPEEDTECH is your one stop solution for everything related to Construction Chemicals, Epoxy, Adhesives, Admixtures, Sealers and other various application like grouting, fixing tile, At SPEEDTECH we have implemented world class practices that ensure our products lasts long. Bid good bye to all your worries with regards to chemicals. Say hello to a worry free future, say hello to SPEEDTECH CHEMBOND





SPEED TECH™
CHEMBOND



Big Vision

To be India’s most trusted and innovative manufacturer of chemical building materials, delivering high-performance solutions that power the future of infrastructure. Our vision is to build a world-class factory that leads with safety, sustainability, and smart automation—setting new benchmarks in quality, efficiency, and environmental responsibility.



SPEED TECH™

CHEMBOND



...PRODUCTS...

TILES ADHESIVE
- ST-250 SILVER
- ST-400 GOLD
- ST-600 PLATINUM
- ST-800 DIAMOND
- BLOCK JOINTING MORTAR

TILES EPOXY
- 3 Part L-poxy

TILES GROUT
- Tiles Grout
- Grout Admixture

TILES CARE
- Tiles Cleaner

TILES ACCESSORIES
- Tiles Spacer
- Tiles Levling Kit

SPEED TECH™
CHEMBOND

CERTIFIED COMPANY

CE

CERTIFIED ISO 9001 : 2015 COMPANY



SPEED TECH™
CHEMBOND

FOR FIXING FLOOR TILES



ST-250 SILVER
TILES ADHESIVE

Tile fixing adhesive for
Internal Floor applications.

PACKING
20 kg

Color : GREY



ST-250 SILVER

Tiling Solutions
Packing 20 Kg

Product Details
SPEEDTECH ST-250 SILVER is a high polymer modified, cement-based til adhesive which is suitable for fixing tiles. cement torrazo, concrete floor, natural stones, vitrified tiles in interior and exterior floor areas.

Application Area
Applying For Flooring tile 24x24, 16x16, 12x12 parking Tiles

Features
- Excellent bond strength
- No shrinkage
- Easy to spread
- Consistent in quality
- Nil wastages
- No curing required
- Single component no hossles of
- mixing the ingredients.

Shelf life & storage
In unopened condition, the shelf life is 12 months from the date of manufacturing Store in a cool & dry place

Technical Information

PROPERTIES	RESULTS
Appearance	Free flowing powder
Colour	Grey
Pot life	3 Hours
Open time	20 Min.
Adjustability time	10 Min.
Trafficable time, Hrs	24
Shear adhesion, dry condition (as per annex B)	1.09 N/mm²
Tensile adhesion, dry condition (as per annex A)	1.0 n/mm²

SPEED TECH™
CHEMBOND

FOR FIXING WALL & VITRIFIED TILES



ST-400 GOLD
TILES ADHESIVE

Tile fixing adhesive for
Internal Floor applications.

PACKING
20 kg

Color : GREY / WHITE



ST-400 GOLD

Tiling Solutions
Packing 20 Kg

Product Details
SPEEDTECH ST-400 GOLD (Grey/White) is a high polymer modified, adhesive for vitrified, granite on wall cladding and floor for internal & external use.

Application Area
Applying for Wall and Vitrified tiles for interior and exterior used (tile on tile 12x24, 800x800, High Depth Elevation, 600x1200mm upto 8 feet)

Features
- Excellent bond strength
- No shrinkage
- Easy to spread
- Consistent in quality
- Nil wastages
- No curing required
- Single component no hossles of
- mixing the ingredients.

Shelf life & storage
In unopened condition, the shelf life is 12 months
from the date of manufacturing Store in a cool & dry place

Technical Information

PROPERTIES	RESULTS
Appearance	Free flowing powder
Colour	White & Grey
Pot life	3 Hours
Open time	20 Min.
Adjustability time	10 Min.
Trafficable time, Hrs	24
Shear adhesiion, (as per annex B) dry condition heat condition wet condition	 >1.50 N/mm² >1.20 N/mm² >1.10 N/mm²
Tensile adhesion, (as per annex A) dry condition wet condition	 >1.40 N/mm² >1.10 N/mm²

SPEED TECH™
CHEMBOND

For Fixing Vitrified tiles



ST-600 PLATINUM

TILES ADHESIVE

Tile fixing adhesive for
Internal Floor applications.

PACKING
20 kg

Color : GREY / WHITE



ST-600 PLATINUM

Product Details

LEXORA ST-600 PLATINUM (Grey & white) is a high polymer modified, white cement based, high performance, high strength and high quality tile adhesive developed to fix glass mosaic, italian marble and special tiles, Suitable for both internal and external, thin bed applications.

Application Area

Applying for wall and vitrifed tiles for exterior and interior used (800x800, 1000x1000, 800x1600 600x1200up to 20 feet) Wooden Planks.

- ► Applying small size marble & granites on wall exterally (up to 800x1200mm)

Features

- Excellent bond strength
- No shrinkage
- Easy to spread
- Consistent in quality
- Nil wastages
- No curing required
- Single component no hossles of
- mixing the ingredients.

Shelf life & storage

In unopened condition, the shelf life is 12 months from the date of manufacturing Store in a cool & dry place

Technical Information

PROPERTIES	RESULTS
Appearance	Free flowing powder
Colour	White & Grey
Pot life	3 Hours
Open time	20 Min.
Adjustability time	10 Min.
Trafficable time, Hrs	24
Shear adhesion, (as per annex B) dry condition heat condition wet condition	 > 1.55 N/mm² > 1.30 N/mm² > 1.15 N/mm²
Tensile adhesion, (as per annex A) dry condition wet condition	 > 1.60 N/mm² > 1.20 N/mm²
Deformablity (as per annex F)	> 2.60 mm

SPEED TECH™
CHEMBOND

For Fixing Marbles & Slabs



ST-800 DIAMOND
TILES ADHESIVE

Tile fixing adhesive for
Internal Floor applications.

PACKING
20 kg



ST-800 DIAMOND

Tiling Solutions
Packing 20 Kg

Product Details
SPEEDTECH ST-800 DIAMOND is a high polymer modified, cement-based til adhesive which is suitable for fixing tiles. cement torrazo, concrete floor, natural stones, vitrified tiles in interior and exterior floor areas.

Application Area
Applying for wall and vitrified for interior and exterior used (1200x1800, 1200x1200, 1200x1600, 1200x1800, 800x2400, slabs) (600x1200 upto 30-40 feets)

Features
- Excellent bond strength
- No shrinkage
- Easy to spread
- Consistent in quality
- Nil wastages
- No curing required
- Single component no hossles of
- mixing the ingredients.

Shelf life & storage
In unopened condition, the shelf life is 12 months
from the date of manufacturing Store in a cool & dry place

Technical Information

PROPERTIES	RESULTS
Appearance	Free flowing powder
Colour	Grey
Pot life	3 Hours
Open time	20 Min.
Adjustability time	10 Min.
Trafficable time, Hrs	24
Shear adhesion, (as per annex B) dry condition heat condition wet condition	 > 1.55 N/mm² > 1.30 N/mm² > 1.15 N/mm²
Tensile adhesion, (as per annex A) dry condition wet condition	 > 1.60 N/mm² > 1.20 N/mm²
Deformablity (as per annex F)	> 2.60 mm

SPEED TECH™
CHEMBOND

For Fixing Blocks



BLOCK JOINTING MORTAR

PACKING
40 kg

Color : GREY



BLOCK JOINTING MORTAR

Description

SPEEDTECH is a non-refractory mortar, used for laying masonry units like AAC blocks. it is a self curing mortar made from cement, selected ne sand and polymeric additives, which ensure good bonding and durable strength between the blocks.

Benefits

- For 4mm bed thickness
- Suitable for indulated blocks
- Block mounting full wall in 2-3 days
- The chiseling and conducting can be carried out after 14days
- The Plastering can be carried out after 7 days
- Can be applied with 90% material transfer
- Self curing adhesive

SPEED TECH™
CHEMBOND

Epoxy 3 Part



Epoxy-3 Part

Stain free grout for
Floor & Wall (3 Part)

PACKING
1 kg



PRODUCT DETAILS

SPEEDTECH Epoxy is a hygienic, hard-wearing, impervious, epoxide resin-based epoxy grout with a high degree of resistance to chemical attack, abrasion and impact. The cured grout does not transfer taints to foodstuffs and does not permit the entry of bacteria or dirt. It is easily maintained in a sterile condition.

TECHNICAL SPECIFICATION

Joint Width	Pot Life @27+-2C°	Cure @27+-2C°	Temperature Resistance	Water Absorption	Specific Gravity
2-20mm	45 minutes	48 hours	Prolonged - 30C°to 150C° Intermittent	Nil(1)	1.75
				Tensile Adhesion (14 days air)	
				Dry condition	Wet condition
Epoxy Grout				>4.5kn	>3.6kn
BS 5980:1980				0.95	0.56

PACKAGING OF SPEEDTECH SERIES

Kit	Filler	Resin	Hardener
1kg	700gm	200ml	100ml

SPEED TECH™
CHEMBOND

High Polymer Tile Grout



Tile Grout

One Pack Water Resistant
Tile Grout

PACKING
1 kg



PRODUCT DETAILS
SPEEDTECH Tile Grout is a Premium fine polymer modified water resistant cement based powder grout use for various applications area.

SHELF LIFE & STORAGE
Shelf life is 12 months from the date of manufacturing in unopened condition. Store in a cool & dry place.

APPLICATION AREA
Glazed Wall tiles | Mosaic | Vitrified | full vitrified | Floor Tiles | Industrial Floor etc.

COLORS
White | Ivory | Grey | C. Brown | Magenta | R. Brown | Beige

Black | Jaisalmer | Terracotta | S. Blue | O.Green | Pink

SPEED TECH™
CHEMBOND

Grout Admix



Grout Admix

For better strength of Grout

PACKING
200 ml



PRODUCT DETAILS
SPEEDTECH Admix is specially designed Latex Admix to be used with Sanded & Unsanded Grout

SHELF LIFE & STORAGE
It improves the performance of Portland cement grouts for all type of ceramic tile, brick, marble, natural stone and agglomerate stone installations

COLORS
- Colour-fastness
- Flexibility
- Compressive strength
- Shock and chemical resistant
- Reduces water absorption
- Easy to clean

COVERAGE
Varies as per application

SPEED TECH™
CHEMBOND

Tiles Cleaner



Tiles Cleaner

Powerful, Heavy Duty
Acid Based Cleaner

PACKING
1 Ltr. / 5 Ltr.



Description

A powerful, heavy duty, acid - based cleaner for ceramic tiled floors and walls. TILE CLEANER is designed for removal of cement film residues, efflorescence and most oxide stains. It may also be used as general purpose cleaner on other acid resistant surface.

Note: Do not use on surfaces that are not resistant to acid such as marble/terrazzo.

Benefits

- Powerful formula
- Fast acting
- Easy to apply
- Removes cement film
- Removes residues, efflorescence and most oxide stains

Use

TILE CLEANER is used for interior and exterior ceramic tiled floors and walls.

Tiles Accessories



Tile Spacer

To Make Space Between Tiles.
Wall Tile, Floor Tiles, Etc...

Available Size :
2mm, 3mm, 4mm,
5mm, 6mm

Pack Size:
100 Pcs. / Pkt





TILES EQUALIZER
(LEVLAR KIT)

Tiles Leveling And Equalizing Surface.

Available Size :
2mm, 3mm, 4mm, 5mm

Pack Size:
clip - 50 Pcs. / Pkt, Wedges - 50 Pcs. / Pkt





Tile Lifters



Tile Leveling Tool



Trowel

Jara Hatke

SPEED TECH™
CHEMBOND

Mfg. & Mktd.By:

SURPRISE SANITATION PVT. LTD.
Bhuj, Kutch - 370 001, Gujarat, INDIA
Customer Care : Cell : +91 87359 94622
Email : speedtechsspl@gmail.com

MAKE IN INDIA

स्वच्छ भारत
एक कदम स्वच्छता की ओर

be vocal support local

21 YEARS OF EXCELLENCE